

Crypton Vertical Applications Technical Specifications		CRYPTON WALL	INCASE FR (PRIVACY CURTAINS)
Applications	Wall Cover	•	•
Fabric Types	Flat Woven Knits Textured (i.e. chenilles, velours, boucle', etc.)	• • •	• • •
Fiber Types	Polyester (virgin or recycled) Polypropylene	• •	• •
Repellency	Oil Drop (AATCC 118, 5 min) Water / IPA Drop (AATCC 193, 5 min)	• •	• •
Cleanability (out of 5 max)	Stain Resistance (Class 4-5) Durable to cleaning with variety of cleaners Acceptable Bleach Cleaning: 10% Bleach for 10 min & rinse (CDC recommendation for C Difficil) High Concentration Bleach or Long-Term Exposure to Bleach (not recommended)	• • •	• • •
Flammability	ASTM E84 - Adhered	•	•
Performance Properties	Stain Resistance (Class 4-5) Resistance to Crocking (AATCC 8, Class 4 Pkg Dye / 5 Soln Dye)	• •	• •
Antimicrobial (Silver Ion Technology)	Resistance to Bacterial Growth (ISO 20743:2007 (E), ATCC 4352) Resistance to Fungal Growth (AATCC 30-1998, AATCC 6275)	• •	• •
Environmental	Third-party GREENGUARD Gold Certified Uses Silver Ion Technology; does not utilize leaching antimicrobials Free of potentially harmful levels of PFOS, PFOA, formaldehyde, heavy metals, phenols, phthalates, odor, and skin sensitizers Does not contain any of the Substances of Very High Concern that have been banned by the European Union's REACH legislation Can be recycled Ongoing recycling program of manufacturing remnants	• • • • • • •	• • • • • • •