

Crypton Vertical A	pplications Technical Specifications	Crypton Wall
Applications	Wall Cover	•
Fabric Types	Flat Woven	
	Knits	•
	Textured (i.e. chenilles, velours, boucle', etc.)	•
FiberTypes	Polyester (virgin or recycled)	
	Polypropylene	•
Repellency	Water / IPA Drop (AATCC 193 ≥ 3,4 max)	•
	Spray Rating: Standard 80 (AATCC 22, 80-100 of 100 max)	•
Cleanability	Stain Resistance (Class 4-5)	•
(out of 5 max)	Durable to cleaning with variety of cleaners	•
	Acceptable Bleach Cleaning:	
	10% Bleach for 10 min & rinse (CDC recommendation for C Difficil)	•
	High Concentration Bleach or Long-Term Exposure to Bleach (not recommended)	
Flammability	ASTM E84 - Adhered	•
Performance Properties	Stain Resistance (Class 4-5)	
	Resistance to Crocking (AATCC 8, Class 4 Pkg Dye / 5 Soln Dye)	•
Silver Ion	Resistance to Antimicrobial (AATCC 100)	
Odor Resistance	Resistance to Bacterial Growth (ISO 20743)	•
	Resistance to Fungal Growth (AATCC 30)	•
	Uses Silver Ion Technology; does not utilize leaching antimicrobials	•
Environmental	PFAS-free	
	Third-party GREENGUARD Gold Certified	•
	Free of potentially harmful levels of formaldehyde, heavy metals, phenols, phthalates, odor and skin sensitizers	•